












TECHNICAL INFORMATION / TEKNISK INFORMATION



BERGO UNIQUE

Material:		ISO2076	Environmentally friendly recyclable / Miljövänlig återvinningsbar UV-stabilized polypropylene. / UV-stabiliserad polypropen.
Size of tile: /Plattans storlek:		EN427	377,2 x 377,2 mm. 1 m ² / box = 7 tiles. 5 m ² / box = 35 tiles.
Thickness of tile: /Plattans tjocklek:		EN428	10,3 mm.
Weight: /Vikt:		EN430	1 tile: 0,412 kg. 1 m ² : 3,064 kg (Consumer pack). 5 m ² : 15,02 kg (Maxi-pack).
Point load: /Punktbelastning:		QUALIFIED TEST BY BERGO	500 ton / 1 m ² = 5000 kg/dm
Light fastness: /Ljusbeständighet:		EN 14836 (>3) ISO 105-B02 (1-8)	4-5 7-8
Weather Fastness /UV- Florida test (1-5):		ASTM D1435 ASTM G154 Cycle A	4/5
Slip resistance: /Halkmotstånd:		DIN51 130 SSEN-13893	R9 / V10 >0,3
Impact resistance: /Slagtålighet:		ISO179/1eA ASTM D746	+23 °C = 20 kJ/m ² / -20 °C = 5 kJ/m ² C15 kJ/m ²
Fire category /Brandklassning:		EN ISO 11925-2	E _{fl}
CE certification:		EN 14041	0402-CPD-P605080A




By normal use and treatment the material guarantee time is 10 years.



Bergo Flooring AB fulfills the requirements of ISO 9001.



Bergo Floors are 100% recyclable.



SYSTEM
2

www.bergoflooring.com

